6E/ECOMPACT





CLASSE 6 E / E COMPACT

Easy technology

The Classe 6 E version has electronic control and automatic dosing, ensuring constant and uniform performance. All versions of the Classe 6 feature a special tray to collect liquids, with one of the highest holding capacities available on the market.

1 C-LEVER (Rancilio Patent) The new steam valve with a special control knob and ergonomic design is complete with open-stay and open-close functions. The valve has a very short travel distance, and is operated by rotating it just 25°. Turning it upwards, it opens and remains in this position. Turned downwards, it automatically closes when released. Rapidity, precision and ergonomics: maximum user comfort for daily work.

V-FLEX is a self-adapting system that harmonizes the operating voltage of the machine with voltage variations in the main power supply. V-flex avoids installation errors and eliminates the fluctuation in the supplied voltage. Machines fitted with V-flex also have an advanced diagnostics function called Easy-Fix, which allows a technician to immediately trace any technical problems and solve them easily.

COMPACT [only for 2G] The compact model, available with 2 groups, has the same potential, but in a smaller housing unit (570 mm), allowing it to be positioned even in restricted spaces.

PLUG & BREW (Rancilio Patent) Installing a Rancilio machine has never been quicker or easier. Dosages and the main functions of the machine can be programmed immediately. Even machines without a display feature allow you to adjust the temperature externally, thanks to a new function that allows boiler pressure to be varied from the control buttons. Standard on all new Classe 6 E versions.



6E. TECHNICAL FEATURES

Technical Features

independent heat exchangers
electric heating
incorporated volumetric pump
boiler pressure gauge
automatic water level control
reduction to 2/3 of maximum power
electronic boiler temperature/pressure control
housing in stainless steel

Endowments, accessories

ENDOWMENTS: 1 filter holder for 2 cups per group, 1 filter holder for 1 cup, 2 steam wands, 1 hot water dispenser programmable for dosage time, coffee tamper, measuring scoop and washing disks, foot extensions.

ACCESSORISES: DP automatic or manual water softener, MD dosing grinder, interchangeable sides.

Colors

stainless steel and steel panels painted metallic grey

Technical Data

2 GROUPS COMPACT

dimensions (wxdxh) 27.1(22.4) x 19.6 x 19.2 inch 690(570) x 500 x 490 mm	weight 121 Lb 55 kg	boiler 1.3 usgal 5 Lt	Hz 50/60
boiler power 3200 W (120 V) - 3000 W	voltage 120 / 220-240 / 380-415 3N		
2 GROUPS			
dimensions (wxdxh) 33.4(28.7) x 19.6 x 19.2 inch 850(730) x 500 x 490 mm	weight 136.6 Lb 62 kg	boiler 2.8 usgal 11 Lt	Hz 50/60
boiler power 3200 W (120 V) - 4300 W 6000 W	voltage 120 / 220-240 / 380-415 3N		
3 GROUPS			
dimensions (wxdxh) 42.9(38.1) x 19.6 x 19.2 inch 1090(970) x 500 x 490 mm	weight 207.2 Lb 94 kg	boiler 4.2 usgal 16 Lt	Hz 50/60
boiler power 6000 W	voltage 220-240 / 380-415 3N		

Standard





6E FFATURES











Advanced diagnostics



Rapid setting

On demand









CUP SSSS | WARMER

Electric cup warmer



GAS

Gas heating not for 2 groups compact



Pod and Capsule Adaptor











